

Aluzinc®

25 YEAR WARRANTY

ArcelorMittal Flat Carbon Europe S.A. provides this warranty to

BUDMAX-METAL Sp. z o.o.
ul. 1 Maja 24
41-940 Piekary Śląskie
Poland


hereafter referred to as “Client”

relating to the quality of its Aluzinc® AZ185-type coated sheets. Subject to the conditions of this document, this warranty covers the structural integrity, in other words the non-perforation and non-rupture due to corrosion of Aluzinc® steel sheet coated with 185 g/m² on both sides according to European standard EN 10346, used for building purposes both indoors and outdoors for a period of 25 years, from the date of shipping by ArcelorMittal Dudelange.

Date 25/03/2013.....

ArcelorMittal Flat Carbon Europe S.A.

The Client


(S).....
Jean-Claude Caillaud / Jean Paul Ordioni
Product, Service & Development / Head of COE: Credit &
/ Encashment

(S).....

If the Client does not return the present document duly dated, initialled and signed by the authorised person(s) within thirty (30) days at the latest of the date of its receipt, the terms and conditions of the present document shall be deemed to have been expressly accepted in full by the Client.

This Warranty is based on the experience gained by ArcelorMittal Flat Carbon Europe S.A through its subsidiary ArcelorMittal Dudelange since it started producing Aluzinc® sheets in 1982.

ArcelorMittal Flat Carbon Europe S.A. subjects its production to accelerated corrosion tests, the results of which act as a guide to continuously improve the quality of its products.

Since production first began, ArcelorMittal Flat Carbon Europe S.A. has been taking samples and placing them in exterior exposure sites. These samples are then checked on a regular basis.

ArcelorMittal Flat Carbon Europe S.A. regularly inspects several buildings constructed using Aluzinc® roofs in various climatic conditions.

In its subsidiary ArcelorMittal Dudelange, ArcelorMittal Flat Carbon Europe S.A. has developed a quality assurance system in line with the requirements of standard ISO 9000.

Warranty Coverage

1. ArcelorMittal Flat Carbon Europe S.A.'s liability in pursuance of the present warranty shall be exclusively limited, at the choice of ArcelorMittal Flat Carbon Europe S.A., either to the cost of repairing the faulty parts of the sheets or to supplying free of charge to the Client's facilities a sufficient quantity of sheets to allow the Client to manufacture components to replace those deemed faulty (profiled trays, panels etc.).
The replacement products must be Aluzinc® sheets of the same type and with the same specifications as the original sheets.
2. Under no circumstances shall ArcelorMittal Flat Carbon Europe S.A. be liable for workforce costs or other costs incurred due to the faulty sheets, or for repairing direct or indirect damage caused by the faulty sheets.
3. All warranty claims shall be sent in writing as soon as possible after the damage occurs to ArcelorMittal Flat Carbon Europe S.A., which shall be allowed to inspect the items deemed to be faulty. The Client shall detail in its claim the precise identification of the material deemed to be non-compliant, including the order number, the invoice number, the coil number, the shipping date and the installation date.
4. The Client shall do everything possible to facilitate the inspection of the material by ArcelorMittal Flat Carbon Europe S.A. and to limit building reinstatement costs.
5. This warranty is granted to the Client of ArcelorMittal Flat Carbon Europe S.A. and to the Client alone. It may only be transferred in the event of a change of control of the Client's company, and within 15 days of the change occurring. Only in this case may the remainder of the warranty be transferred to the Client's successor. The Client may not provide his own customers with warranties relating to the products sold by ArcelorMittal Flat Carbon Europe S.A. and which would exceed the terms of the present warranty.
6. The warranty covers all products shipped from the date of signing of this warranty certificate. ArcelorMittal Flat Carbon Europe S.A. reserves the right to modify the terms of the warranty at any time, with the exception of sheets already delivered or orders already placed.
7. It is agreed that the warranty shall not apply in the event of damage caused during transportation.
8. In the event of a dispute resulting from or in connection with this warranty, the Courts of the City of Luxembourg shall have exclusive jurisdiction in relation thereto. This warranty is governed by Luxembourg law. Only the French version of this text shall be deemed authentic.

Application conditions

The warranty applies to all buildings:

1. Situated in locations with a normal atmospheric corrosivity category (C1 ... C4 as per EN ISO 12944-2); in other words, excluding those in highly polluted areas or areas less than 2,0 km from the seafront and/or subjected to permanent spraying with fresh water or salt water (corrosivity category C5-I and C5-M as per EN ISO 12944-2).
2. Exposed to moderate corrosive emissions, in other words excluding those subject to the fallout of corrosive chemical products of any kind, smoke or rainwater containing carbon, deposit or particles of heavy metals such as iron or copper, alkaline products such as ash, cement dust or animal excrement.
3. When used indoors, the warranty shall apply provided no emissions or condensates of any kind are present inside the building.

Construction rules

To ensure the warranty applies, the following rules must be complied with during installation:

1. Internal bending radius must be at least equal to the figures in the following table:

Grade	Thickness $\leq 0,75$ mm	Thickness $> 0,75$ mm
DX51D – DX56D S250GD - S380GD	$r = 2 \times \text{thickness}$	$r = 4 \times \text{thickness}$
S550GD « full hard »	$r = 5 \times \text{thickness}$	Not applicable

2. For use as roofing, this shall be designed so that there is no possibility of water or waste – organic or otherwise - stagnating on the Aluzinc®, including right on the fixings and under the profile overlaps.
3. The slope of the roof shall be at least 2 degrees.
4. Fixings shall not contain any copper or lead parts in contact with Aluzinc® sheet, or any material liable to cause corrosive run-off onto the Aluzinc® sheet. They shall be suitably shaped to prevent any local indentation of the Aluzinc® sheets, which may prevent rainwater from draining off freely.
5. Forming shall occur without subjecting the Aluzinc® sheets to high tensile stress or alternating bending stress.
6. Aluzinc® sheets that have sustained damage of a mechanical or chemical nature during forming, transportation, storage or assembly shall not be used. Sheets that sustain damage after assembly shall be replaced before construction work comes to an end.
7. All contact with wet insulation materials, impregnated wood or other corrosive products is to be avoided.
8. After fitting, all tools, debris and miscellaneous items must be removed. Pencil or pen marks and any other type of marking must be removed. Aluzinc® products are to be inspected annually by the Client or its authorised representative. They are to be cleaned regularly and any accidental damage noted is to be repaired (scratches, dents, bulges, etc.).